



## **BORE WELDER - FEATURES**



### **FEATURES:**

 Smooth, high quality welding on internal bores from 1.25"-15" (32-381 mm).

BWS-2000: 1.25"-15" (32-381mm) BWS-2000-045: 1.8"-15" (46-381mm)

Optional accessories for internal diameters from 16"-24" (406-610 mm), external diameters and face welding are also available.

- Easy operation. Simply measure diameter, find setting on the chart and set rotation knob.
- Adds axial feed and rotary motion to existing MIG welder.

- Telescoping extension tube allows multiple in-line welding with one easy set up.
- Reaches 24" (609mm) into a bore with a 7" (177mm) stroke.
- Extension tube is reversible to allow welding of two separate parallel bores.
- · Interfaces with boring bars.
- Kit accommodates various size of welding wire:

BWS-2000: .030 mm BWS-2000-045: .045 mm

.035 mm diameter wire available by request.

### Kit Includes:

- · Remote Weld Switch.
- Conduit Assembly & Support w/Aux. Support Rod.
- Tack Nut.
- Tool Kit.
- Large Diameter Torch

- "T" Base w/Tack Plate.
- Extra Nozzles, Tips, and Diffusers to support 1.25" or 1.8" to 15" (32-381 or 46-381mm) diameters. (5 stub diffusers, 10 .8 mm stub tips, 5 stub nozzles, 10 .8 mm tips, 5 nozzles, 5 mini nozzles, 5 mini diffusers).





# **BORE WELDER - TECHNICAL DATA**

### TECHNICAL DATA:

### BWS-2000 Bore Welding System Bore Welding System for .030"-.035" Wire

Current Rating: 150 amp, 60%duty cycle

**Net Weight:** 25 lbs. (11 kg.)

Shipping Weight: 70 lbs. (34 kg.)

Wire Diameters: .030 and .035

**Diameter Range:** 1.25" to 15" (32- 381mm)

(up to 24" [610mm] with optional accessories)

BWS-2000-045

Bore Welding System for .045" Wire

Current Rating: 200 amp, 60%duty cycle

Net Weight: 25 lbs. (11 kg.)

Shipping Weight: 70 lbs. (34 kg.)

Wire Diameters: .030 to .045

**Diameter Range:** 1.8" to 15" (46-381 mm)

(up to 24" [610mm] with optional accessories)





One Quick Setup - will attach to your Boring Bar Kit.





# **BORE WELDER - ACCESSORIES**

#### Optional Accessories to weld from 15" to 24" (381-610 mm):

ItemDescriptionQuantityBWS-1042Extension Tube2BWS-A1198" (203mm) Radial Support Extender1

Additional Options Available:
BWS-A129 Auto Skip Option
BWS-A108 Centering Cone Set

#### Additional Accessories Available:



BWS-A127 Face Torch
Optional face torch attaches to your
Bore Welder and will automatically
weld faces from 0-24" (0-610mm).



Boring Bar Adaptor Kits Boring Bar Adaptor Kits provide easy, one-step setup. (Part number varies depending on Boring Bar Kit.)



BWS-A114 O.D. Torch Attachment for performing external outside diameter welds. O.D. Torch 0-12" (0-305mm)

### **Welding Tips**

**Stub Tips:** 

BWS-1058 .030 (.8mm) BWS-1059 .035 (.9mm) BWS-1060 .045 (1.2mm)

Standard Tips:

BWS-1061 .030 (.8mm) BWS-1062 .035 (.9mm) BWS-1063 .045 (1.2mm)

#### Welding Nozzles and Diffusers

Mini Nozzle:

BWS-1092 1.25"-2" (32-50mm)

Stub Nozzle:

BWS-1066 Use for small

diameters

Standard Nozzle:

BWS-1067 Use for large


diameters


Mini Diffuser:

BWS-1093 1.25"-2" (32-50mm)

Diffuser:

BWS-1057 Use with all torches





Call factory for specials, boring bar systems and components or power supply wire feeder options. 1-800-245-3186 or 412-331-1776